

Multi-Material - 5XD



AlTiN Coated

Multi-Material, Solid Carbide, 142° Point, 5X Dia., 30° Helix (.5312-.6299)

Drill Size	Decimal Equiv	Flute Length	Drill Depth	OAL	Shank \varnothing	AlTiN Coated Part #
17/32	.5312	3.030	2.420	5.280	35/64	RDH1293
13.50MM	.5315	77	62	134	14.0	RDH1295
13.70MM	.5394	77	62	134	14.0	RDH1297
35/64	.5469	3.030	2.420	5.280	35/64	RDH1299
14.00MM	.5512	77	62	134	14.0	RDH1301
9/16	.5625	3.150	2.520	5.510	5/8	RDH1303
14.50MM	.5709	80	64	140	16.0	RDH1305
14.70MM	.5787	80	64	140	16.0	RDH1307
15.00MM	.5905	80	64	140	16.0	RDH1309
19/32	.5938	3.230	2.580	5.750	5/8	RDH1311
15.30MM	.6024	82	66	146	16.0	RDH1313
15.50MM	.6102	82	66	146	16.0	RDH1315
15.70MM	.6181	82	66	146	16.0	RDH1317
5/8	.6250	3.230	2.580	5.750	5/8	RDH1319
16.00MM	.6299	82	66	146	16.0	RDH1321

Carbide Drills



Speeds & Feeds page 327.

For detailed tolerance information, see page 327.