

# MIRACLE END MILL FOR HIGH HARDNESS STEEL


CARBIDE

## VCLD

End mill, Long cut length, 6 flute



Carbon Steel, Alloy Steel, Cast Iron (<30HRC)	Tool Steel, Pre-Hardened Steel, Hardened Steel (<=45HRC)	Hardened Steel (<=55HRC)	Hardened Steel (>55HRC)	Austenitic Stainless Steel	Titanium Alloy, Heat Resistant Alloy	Copper Alloy	Aluminium Alloy
○	◎	◎	◎				



SQUARE

BALL

	DC ≤ 12	DC > 12			
	$\begin{matrix} 0 \\ -0.020 \end{matrix}$	$\begin{matrix} 0 \\ -0.030 \end{matrix}$			
	DCON=6	8 ≤ DCON ≤ 10	12 ≤ DCON ≤ 16	20 ≤ DCON ≤ 25	
	$\begin{matrix} 0 \\ -0.008 \end{matrix}$	$\begin{matrix} 0 \\ -0.009 \end{matrix}$	$\begin{matrix} 0 \\ -0.011 \end{matrix}$	$\begin{matrix} 0 \\ -0.013 \end{matrix}$	

● Ideal for tool steel and hardened materials machining

RADIUS

TAPER

Unit : mm

Order Number	DC	APMX	LF	DCON	No. of Flutes	Stock	Type
VCLDD0600	6	26	70	6	6	●	1
VCLDD0800	8	36	90	8	6	●	1
VCLDD1000	10	46	100	10	6	●	1
VCLDD1200	12	56	110	12	6	●	1
VCLDD1600	16	66	130	16	6	●	1
VCLDD2000	20	76	140	20	6	●	1
VCLDD2500	25	92	180	25	6	●	1

SOLID END MILLS

## RECOMMENDED CUTTING CONDITIONS

Work material	Alloy steel, Tool steel, Pre-hardened steel		Hardened steel (45—55HRC)		Hardened steel (55—62HRC)		Hardened steel (62—70HRC)	
	AISI H13, AISI W1-10, AISI P21		AISI H13		AISI D2		AISI W1, AISI M2	
Dia. DC (mm)	Revolution (min <sup>-1</sup> )	Feed rate (mm/min)	Revolution (min <sup>-1</sup> )	Feed rate (mm/min)	Revolution (min <sup>-1</sup> )	Feed rate (mm/min)	Revolution (min <sup>-1</sup> )	Feed rate (mm/min)
6	2100	450	1600	330	1300	240	1100	190
8	1600	430	1200	310	1000	230	800	170
10	1300	420	960	290	800	220	640	150
12	1100	380	800	260	660	200	530	140
16	800	310	600	220	500	160	400	120
20	640	270	480	190	400	140	320	110
25	510	230	380	160	320	120	260	90

Depth of cut				
	3DC—4DC		3DC—4DC	

DC: Dia.

- 1) If the depth of cut is shallow, the revolution and feed rate can be increased.
- 2) If the rigidity of the machine or the work materials installation is very low, or chattering and noise are generated, reduce the revolution and feed rate proportionately.

● : Inventory maintained in Japan.