

MIRACLE END MILLS

CARBIDE

VC2MB

Ball nose end mill, Medium cut length, 2 flute

VC2MDB

Ball nose, Medium cut length, 2 flute, Strong geometry type


RECOMMENDED CUTTING CONDITIONS

R PRFRAD (mm)	Alloy steel, Tool steel, Pre-hardened steel AISI H13, AISI W1-10, AISI P21				Hardened steel (45—55HRC) AISI H13					
	$\alpha \leq 15^\circ$		$\alpha > 15^\circ$		Depth of cut (mm)	$\alpha \leq 15^\circ$		$\alpha > 15^\circ$		Depth of cut (mm)
	Revolution (min ⁻¹)	Feed rate (mm/min)	Revolution (min ⁻¹)	Feed rate (mm/min)		Revolution (min ⁻¹)	Feed rate (mm/min)	Revolution (min ⁻¹)	Feed rate (mm/min)	
R 0.5	40000	5600	40000	3200	0.06	40000	5600	40000	3000	0.06
R 0.75	40000	6500	40000	3200	0.09	40000	6500	32000	3200	0.09
R 1	40000	6500	39000	3800	0.11	40000	6500	31000	3500	0.11
R 1.5	40000	7500	27000	4300	0.13	32000	6000	22000	3400	0.13
R 2	32000	7500	20000	3600	0.15	25000	6000	16000	2700	0.15
R 2.5	25000	6000	16000	2900	0.20	20000	5400	13000	2300	0.20
R 3	21000	5800	13000	2600	0.25	17000	4700	10000	2000	0.25
R 4	16000	4500	10000	2000	0.30	13000	3600	8000	1500	0.30
R 5	13000	3600	8000	1700	0.50	10000	2900	6400	1200	0.50
R 6	9000	2500	6000	1300	0.50	7200	2000	4800	1000	0.50

≤ 0.2PRFRAD
Please refer to the list above for depth of cut.
PRFRAD: Radius

- 1) α is the inclination angle of the machined surface.
- 2) If the depth of cut is shallow, the revolution and feed rate can be increased.
- 3) If the rigidity of the machine or the work materials installation is very low, or chattering and noise are generated, reduce the revolution and feed rate proportionately.

SOLID END MILLS



Using general machining center or NC milling machine.

Roughing (Depth of cut ≤ 0.8R)				
R PRFRAD (mm)	Carbon steel, Cast iron, Alloy steel (—30HRC) AISI 1050, AISI No 35 B, AISI P20		Alloy steel, Tool steel, Pre-hardened steel AISI H13, AISI W1-10, AISI P21	
	Revolution (min ⁻¹)	Feed rate (mm/min)	Revolution (min ⁻¹)	Feed rate (mm/min)
R 0.5	—	—	—	—
R 1	8800	150	7000	110
R 2	5800	280	4400	230
R 3	4200	340	3100	240
R 4	3200	360	2400	280
R 5	2500	340	1900	260
R 6	2100	300	1600	220
R 8	1500	210	1200	170
R10	1200	170	960	130
R12.5	950	130	770	110