

Straight Shank Drills

**Jobbers Length
Screw Machine Length
Taper Length**

**List No. 500, 501, 501A, 599
List No. 561, 563
List No. 531**

Straight Shank Cobalt Drills

**Jobbers Length
Screw Machine Length
Taper Length**

**List No. 6501, 6520, 599
List No. 6563
List No. 6531**

Workpiece Material			Carbon Steels		Alloy Steels Hardened Steels		Mold Steels Stainless Steels		Titanium Alloys ¹⁾ High Temperature Alloys ¹⁾		Cast Irons		Aluminum Alloys Nonferrous Metals	
Speed (SFM)			50 - 65 SFM		40 - 52 SFM		30 - 40 SFM		10 - 20 SFM		55 - 72 SFM		83 - 115 SFM	
Drill Diameter			50 - 65 SFM		40 - 52 SFM		30 - 40 SFM		10 - 20 SFM		55 - 72 SFM		83 - 115 SFM	
Fractional	Metric mm	Decimal	RPM	Feed (IPR)	RPM	Feed (IPR)	RPM	Feed (IPR)	RPM	Feed (IPR)	RPM	Feed (IPR)	RPM	Feed (IPR)
—	1	0.0394	4,800	0.0008	3,800	0.0007	2,900	0.0006	1,500	0.0003	5,300	0.0010	8,100	0.0007
1/16	1.588	0.0625	3,400	0.0013	2,700	0.0011	2,100	0.0009	1,000	0.0005	3,800	0.0015	5,800	0.0011
—	2	0.0787	2,900	0.0016	2,300	0.0013	1,700	0.0012	720	0.0006	3,200	0.0020	4,900	0.0014
—	3	0.1181	2,100	0.0028	1,700	0.0023	1,300	0.0021	480	0.0009	2,300	0.0034	3,600	0.0024
1/8	3.175	0.1250	2,000	0.0029	1,700	0.0023	1,200	0.0022	460	0.0010	2,200	0.0036	3,500	0.0025
—	5	0.1969	1,300	0.0042	1,000	0.0037	760	0.0033	290	0.0015	1,400	0.0053	2,200	0.0038
1/4	6.35	0.2500	1,100	0.0047	800	0.0044	610	0.0038	230	0.0020	1,120	0.0064	1,750	0.0044
—	8	0.3150	800	0.0059	640	0.0050	480	0.0044	180	0.0025	900	0.0074	1,400	0.0051
3/8	9.525	0.3750	680	0.0065	540	0.0055	400	0.0049	160	0.0030	740	0.0082	1,200	0.0054
—	10	0.3937	640	0.0068	510	0.0057	380	0.0050	150	0.0032	700	0.0084	1,100	0.0057
—	12	0.4724	530	0.0074	420	0.0064	320	0.0057	120	0.0040	580	0.0095	900	0.0066
1/2	12.7	0.5000	510	0.0076	400	0.0066	310	0.0057	120	0.0043	550	0.0099	860	0.0069
5/8	15.875	0.6250	410	0.0089	330	0.0076	250	0.0065	100	0.0050	450	0.0115	690	0.0086
—	16	0.6299	400	0.0091	320	0.0078	240	0.0067	90	0.0050	440	0.0116	680	0.0087

- 1) The cutting condition of Titanium Alloys and Nickel Alloys are for HSS-Co drills only.
- 2) The above values apply when coolant is used in a vertical machine. In a horizontal machine or deep hole, use pecking.
- 3) Adjust drilling condition when unusual vibration or different sound occurs.

Straight Shank Drills TiN Coated

**Jobbers Length
Screw Machine Length**

**List No. 501P, 520P
List No. 561P**

Workpiece Material			Carbon Steels		Alloy Steels		Die Steels Hardened Steels Stainless Steels		Cast Irons		Aluminum Alloys Nonferrous Metals	
Speed (SFM)			60 - 85 SFM		47 - 65 SFM		36 - 48 SFM		66 - 90 SFM		100 - 140 SFM	
Drill Diameter			60 - 85 SFM		47 - 65 SFM		36 - 48 SFM		66 - 90 SFM		100 - 140 SFM	
Fractional	Metric mm	Decimal	RPM	Feed (IPR)	RPM	Feed (IPR)	RPM	Feed (IPR)	RPM	Feed (IPR)	RPM	Feed (IPR)
—	1	0.0394	5,800	0.0008	4,600	0.0007	3,500	0.0006	6,400	0.0010	9,800	0.0007
1/16	1.588	0.0625	4,100	0.0013	3,200	0.0011	2,500	0.0009	4,400	0.0015	7,000	0.0011
—	2	0.0787	3,500	0.0016	2,800	0.0013	2,000	0.0012	3,800	0.0020	5,900	0.0014
—	3	0.1181	2,500	0.0028	2,000	0.0023	1,500	0.0021	2,800	0.0034	4,300	0.0024
1/8	3.175	0.1250	2,400	0.0029	2,000	0.0023	1,400	0.0022	2,600	0.0036	4,200	0.0025
—	5	0.1969	1,600	0.0042	1,200	0.0037	910	0.0033	1,700	0.0053	2,600	0.0038
1/4	6.35	0.2500	1,300	0.0047	1,000	0.0044	730	0.0038	1,300	0.0064	2,100	0.0044
—	8	0.3150	1,000	0.0059	770	0.0050	580	0.0044	1,100	0.0074	1,700	0.0051
3/8	9.525	0.3750	820	0.0065	650	0.0055	480	0.0049	890	0.0082	1,400	0.0054
—	10	0.3937	770	0.0068	610	0.0057	460	0.0050	840	0.0084	1,300	0.0057
—	12	0.4724	640	0.0074	500	0.0064	380	0.0057	700	0.0095	1,100	0.0066
1/2	12.7	0.5000	610	0.0076	490	0.0066	370	0.0057	670	0.0099	1,000	0.0069
5/8	15.875	0.6250	500	0.0089	400	0.0076	300	0.0065	540	0.0115	830	0.0086
—	16	0.6299	480	0.0091	380	0.0078	290	0.0067	530	0.0116	820	0.0087

- 1) The above values apply when coolant is used in a vertical machine. In a horizontal machine or deep hole, use pecking.
- 2) Adjust drilling condition when unusual vibration or different sound occurs.