

5-Flute



AITiN Coated

5-Flute, Square End & Corner Radius, 45° Helix

Cutter ø	Decimal Equiv	Flute Length	OAL	Radius	Shank ø	Uncoated Part #	AITiN Coated Part #
1/8	.1250	1/4	1-1/2	—	1/8	—	RE17708
1/8	.1250	1/4	1-1/2	.010	1/8	—	RE20408
1/8	.1250	1/2	1-1/2	—	1/8	—	RE17908
1/8	.1250	1/2	1-1/2	.010	1/8	—	RE20608
3/16	.1875	3/8	2	—	3/16	—	RE17712
3/16	.1875	3/8	2	.010	3/16	—	RE20412
3/16	.1875	3/4	2	—	3/16	—	RE17912
3/16	.1875	3/4	2	.010	3/16	—	RE20612
1/4	.2500	1/2	2	—	1/4	—	RE17716
1/4	.2500	1/2	2	.020	1/4	—	RE20416
1/4	.2500	3/4	2-1/2	—	1/4	—	RE17916
1/4	.2500	3/4	2-1/2	.020	1/4	—	RE20616
5/16	.3125	1/2	2	—	5/16	—	RE17720
5/16	.3125	1/2	2	.020	5/16	—	RE20420
5/16	.3125	7/8	2-1/2	—	5/16	—	RE17920
5/16	.3125	7/8	2-1/2	.020	5/16	—	RE20620
3/8	.3750	5/8	2	—	3/8	—	RE17724
3/8	.3750	5/8	2	.020	3/8	—	RE20424
3/8	.3750	1	2-1/2	—	3/8	—	RE17924
3/8	.3750	1	2-1/2	.020	3/8	—	RE20624
7/16	.4375	5/8	2-1/2	—	7/16	—	RE17728
7/16	.4375	5/8	2-1/2	.020	7/16	—	RE20428
1/2	.5000	5/8	2-1/2	—	1/2	—	RE17732
1/2	.5000	5/8	2-1/2	.040	1/2	—	RE20432
1/2	.5000	1-1/4	3	—	1/2	—	RE17932
1/2	.5000	1-1/4	3	.040	1/2	—	RE20632
5/8	.6250	3/4	3	—	5/8	—	RE17740
5/8	.6250	3/4	3	.040	5/8	—	RE20440
5/8	.6250	1-5/8	3-1/2	—	5/8	—	RE17940
5/8	.6250	1-5/8	3-1/2	.040	5/8	—	RE20640
3/4	.7500	1	3	—	3/4	—	RE17748
3/4	.7500	1	3	.040	3/4	—	RE20448
3/4	.7500	1-5/8	4	—	3/4	—	RE17948
3/4	.7500	1-5/8	4	.040	3/4	—	RE20648

Carbide Endmills



Speeds & Feeds page 216.

Tolerances	Diameter	Shank	Radius
1/8"-1/2"	+0.000, -0.002	-0.0001, -0.0004	+0.001, -0.001
5/8"-3/4"	+0.000, -0.003	-0.0001, -0.0004	+0.001, -0.001