

## Aluminum & Non-Ferrous



ZrN Coated-Plain Shank



ZrN Coated-Weldon Shank

### Aluminum & Non-Ferrous, 3-Flute, Square and Corner Radius, 37° Helix

Cutter ø	Decimal Equiv	Flute Length	OAL	Corner Radius	Shank ø	ZrN Coated	
						Plain Shank Part #	Weldon Shank Part #
1/8	.1250	1/4	1-1/2	—	1/8	<a href="#">REX3000</a>	—
1/8	.1250	3/8	1-1/2	—	1/8	<a href="#">REX3001</a>	—
1/8	.1250	3/8	1-1/2	.015	1/8	<a href="#">REX3002</a>	—
1/8	.1250	1/2	2	—	1/8	<a href="#">REX3003</a>	—
3/16	.1880	5/16	2	—	3/16	<a href="#">REX3004</a>	—
3/16	.1880	9/16	2	—	3/16	<a href="#">REX3005</a>	—
3/16	.1880	9/16	2	.015	3/16	<a href="#">REX3006</a>	—
3/16	.1880	3/4	2-1/2	—	3/16	<a href="#">REX3007</a>	—
1/4	.2500	1/2	2	—	1/4	<a href="#">REX3008</a>	—
1/4	.2500	1/2	2	.015	1/4	<a href="#">REX3009</a>	—
1/4	.2500	3/4	2-1/2	—	1/4	<a href="#">REX3010</a>	—
1/4	.2500	3/4	2-1/2	.015	1/4	<a href="#">REX3011</a>	—
1/4	.2500	3/4	2-1/2	.030	1/4	<a href="#">REX3012</a>	—
1/4	.2500	1	3	—	1/4	<a href="#">REX3013</a>	—
1/4	.2500	1	3	.015	1/4	<a href="#">REX3014</a>	—
1/4	.2500	1	3	.030	1/4	<a href="#">REX3015</a>	—
5/16	.3125	15/16	2-1/2	—	5/16	<a href="#">REX3016</a>	—
5/16	.3125	15/16	2-1/2	.015	5/16	<a href="#">REX3017</a>	—
5/16	.3125	15/16	2-1/2	.030	5/16	<a href="#">REX3018</a>	—
5/16	.3125	1-3/8	3	—	5/16	<a href="#">REX3019</a>	—
3/8	.3750	1/2	2	—	3/8	<a href="#">REX3020</a>	—
3/8	.3750	1/2	2	.015	3/8	<a href="#">REX3021</a>	—
3/8	.3750	15/16	2-1/2	—	3/8	<a href="#">REX3022</a>	<a href="#">REX3023</a>
3/8	.3750	15/16	2-1/2	.015	3/8	<a href="#">REX3024</a>	—
3/8	.3750	15/16	2-1/2	.030	3/8	<a href="#">REX3025</a>	—
3/8	.3750	15/16	2-1/2	.060	3/8	<a href="#">REX3026</a>	—
3/8	.3750	1-1/8	3	—	3/8	<a href="#">REX3027</a>	—
3/8	.3750	1-1/8	3	.015	3/8	<a href="#">REX3028</a>	—
3/8	.3750	1-1/8	3	.030	3/8	<a href="#">REX3029</a>	—
3/8	.3750	1-1/8	3	.060	3/8	<a href="#">REX3030</a>	—
3/8	.3750	1-1/2	3-1/2	—	3/8	<a href="#">REX3031</a>	<a href="#">REX3032</a>
3/8	.3750	1-1/2	3-1/2	.015	3/8	<a href="#">REX3033</a>	—
3/8	.3750	1-1/2	3-1/2	.030	3/8	<a href="#">REX3034</a>	—
3/8	.3750	1-1/2	3-1/2	.060	3/8	<a href="#">REX3035</a>	—
3/8	.3750	2	4	—	3/8	<a href="#">REX3036</a>	—
1/2	.5000	5/8	2-1/2	—	1/2	<a href="#">REX3037</a>	—
1/2	.5000	5/8	2-1/2	.030	1/2	<a href="#">REX3038</a>	—
1/2	.5000	5/8	3	—	1/2	<a href="#">REX3039</a>	—



Speeds & Feeds page 186.

Tolerances	Diameter	Shank	Radius
Fractional	-0.0001, -0.0004	h6	+0.0015, -0.0015

For specific shank tolerance information please see page 200.