



ZrN Coated-Plain Shank



ZrN Coated-Weldon Shank

Aluminum & Non-Ferrous, 3-Flute, Square and Corner Radius, 37° Helix

Cutter Ø	Decimal Equiv	Flute Length	OAL	Corner Radius	Shank Ø	ZrN Coated	
						Plain Shank Part #	Weldon Shank Part #
1/2	.5000	5/8	3	.030	1/2	REX3040	—
1/2	.5000	5/8	3	.125	1/2	REX3041	—
1/2	.5000	1	3	—	1/2	REX3042	REX3043
1/2	.5000	1	3	.015	1/2	REX3044	—
1/2	.5000	1	3	.030	1/2	REX3045	—
1/2	.5000	1	3	.060	1/2	REX3046	—
1/2	.5000	1	3	.125	1/2	REX3047	—
1/2	.5000	1-1/4	3	—	1/2	REX3048	—
1/2	.5000	1-1/4	3	.015	1/2	REX3049	—
1/2	.5000	1-1/4	3	.030	1/2	REX3050	—
1/2	.5000	1-1/4	3	.060	1/2	REX3051	—
1/2	.5000	1-1/4	3	.125	1/2	REX3052	—
1/2	.5000	1-1/2	3-1/2	—	1/2	REX3053	REX3054
1/2	.5000	1-1/2	3-1/2	.030	1/2	REX3055	—
1/2	.5000	1-1/2	3-1/2	.060	1/2	REX3056	—
1/2	.5000	1-1/2	3-1/2	.125	1/2	REX3057	—
1/2	.5000	2	4	—	1/2	REX3058	REX3059
1/2	.5000	2	4	.015	1/2	REX3060	—
1/2	.5000	2	4	.030	1/2	REX3061	—
1/2	.5000	2	4	.060	1/2	REX3062	—
1/2	.5000	2	4	.125	1/2	REX3063	—
1/2	.5000	2-1/2	5	—	1/2	REX3064	—
1/2	.5000	2-1/2	5	.030	1/2	REX3065	—
5/8	.6250	1-1/4	3-1/2	—	5/8	REX3066	—
5/8	.6250	1-1/4	3-1/2	.030	5/8	REX3067	—
5/8	.6250	1-1/4	3-1/2	.125	5/8	REX3068	—
5/8	.6250	1-7/8	4	—	5/8	REX3069	REX3070
5/8	.6250	1-7/8	4	.030	5/8	REX3071	—
5/8	.6250	1-7/8	4	.125	5/8	REX3072	—
5/8	.6250	2-1/2	5	—	5/8	REX3073	—
5/8	.6250	2-1/2	5	.030	5/8	REX3074	—
3/4	.7500	1-5/8	4	—	3/4	REX3075	REX3076
3/4	.7500	1-5/8	4	.030	3/4	REX3077	—
3/4	.7500	1-5/8	4	.060	3/4	REX3078	—
3/4	.7500	1-5/8	4	.125	3/4	REX3079	—
3/4	.7500	2-1/4	5	—	3/4	REX3080	REX3081
3/4	.7500	2-1/4	5	.030	3/4	REX3082	—



Tolerances	Diameter	Shank	Radius
Fractional	-0.0001, -0.0004	h6	+0.0015, -0.0015

For specific shank tolerance information please see page 200.



Speeds & Feeds page 186.