



Uncoated-Type 1

Uncoated-Type 2

### Micro-Drills, Solid Carbide, 130° Point, 35° Helix (1043-.1250)

Drill Size	Decimal Equiv	Flute Length	OAL	Shank ø	Drill Type	Uncoated Part #
2.65MM	.1043	.480	1.5	1/8	Type 2	<a href="#">RMD1043</a>
2.70MM	.1063	.480	1.5	1/8	Type 2	<a href="#">RMD1063</a>
#36	.1065	.480	1.5	1/8	Type 2	<a href="#">RMD1065</a>
2.75MM	.1083	.480	1.5	1/8	Type 2	<a href="#">RMD1083</a>
7/64	.1094	.480	1.5	1/8	Type 2	<a href="#">RMD1094</a>
#35	.1100	.480	1.5	1/8	Type 2	<a href="#">RMD1100</a>
2.80MM	.1102	.480	1.5	1/8	Type 2	<a href="#">RMD1102</a>
#34	.1110	.480	1.5	1/8	Type 2	<a href="#">RMD1110</a>
2.85MM	.1122	.480	1.5	1/8	Type 2	<a href="#">RMD1122</a>
#33	.1130	.480	1.5	1/8	Type 2	<a href="#">RMD1130</a>
2.90MM	.1142	.480	1.5	1/8	Type 2	<a href="#">RMD1142</a>
#32	.1160	.480	1.5	1/8	Type 2	<a href="#">RMD1160</a>
2.95MM	.1161	.480	1.5	1/8	Type 2	<a href="#">RMD1161</a>
3.00MM	.1181	.480	1.5	1/8	Type 2	<a href="#">RMD1181</a>
#31	.1200	.480	1.5	1/8	Type 2	<a href="#">RMD1200</a>
3.05MM	.1201	.480	1.5	1/8	Type 2	<a href="#">RMD1201</a>
3.10MM	.1220	.480	1.5	1/8	Type 2	<a href="#">RMD1220</a>
3.15MM	.1240	.480	1.5	1/8	Type 2	<a href="#">RMD1240</a>
1/8	.1250	.480	1.5	1/8	Type 2	<a href="#">RMD1250</a>

Tolerances	Drill ø	Shank ø
All Sizes	+0.000, -.0005	+0.000, -.0003



Speeds & Feeds page 325.