

Double Margin - 3XD



AITiNX Coated

Double Margin, Solid Carbide, Coolant Fed, 142° Point, 3X Dia., 30° Helix (1181-.2205)

Drill Size	Decimal Equiv	Flute Length	Drill Depth	OAL	Shank ø	AITiNX Coated Part #
3.00MM	.1181	20	14	62	3.0	RDX3200
#31	.1200	.787	.551	2.440	1/8	RDX3201
3.10MM	.1220	20	14	62	4.0	RDX3202
1/8	.1250	.787	.551	2.440	1/8	RDX3203
3.20MM	.1260	20	14	62	4.0	RDX3204
#30	.1285	.787	.551	2.440	5/32	RDX3205
3.30MM	.1299	20	14	62	4.0	RDX3206
3.40MM	.1339	20	14	62	4.0	RDX3207
#29	.1360	.787	.551	2.440	5/32	RDX3208
3.50MM	.1378	20	14	62	4.0	RDX3209
9/64	.1406	.787	.551	2.440	5/32	RDX3210
3.60MM	.1417	20	14	62	4.0	RDX3211
3.70MM	.1457	20	14	62	4.0	RDX3212
3.80MM	.1496	24	17	66	4.0	RDX3213
#24	.1520	.945	.669	2.600	5/32	RDX3214
3.90MM	.1535	24	17	66	4.0	RDX3215
5/32	.1562	.945	.669	2.600	5/32	RDX3216
4.00MM	.1575	24	17	66	4.0	RDX3217
#21	.1590	.945	.669	2.600	3/16	RDX3218
4.10MM	.1614	24	17	66	5.0	RDX3219
4.20MM	.1654	24	17	66	5.0	RDX3220
4.30MM	.1693	24	17	66	5.0	RDX3221
11/64	.1719	.945	.669	2.600	3/16	RDX3222
4.40MM	.1732	24	17	66	5.0	RDX3223
4.50MM	.1772	24	17	66	5.0	RDX3224
4.60MM	.1811	24	17	66	5.0	RDX3225
4.70MM	.1850	24	17	66	5.0	RDX3226
3/16	.1875	1.102	.787	2.600	3/16	RDX3227
4.80MM	.1890	28	20	66	5.0	RDX3228
4.90MM	.1929	28	20	66	5.0	RDX3229
5.00MM	.1968	28	20	66	5.0	RDX3230
5.10MM	.2008	28	20	66	6.0	RDX3231
13/64	.2031	1.102	.787	2.598	1/4	RDX3232
5.20MM	.2047	28	20	66	6.0	RDX3233
5.30MM	.2087	28	20	66	6.0	RDX3234
5.40MM	.2126	28	20	66	6.0	RDX3235
5.50MM	.2165	28	20	66	6.0	RDX3236
7/32	.2187	1.102	.787	2.598	1/4	RDX3237
5.60MM	.2205	28	20	66	6.0	RDX3238



Carbide Drills



Speeds & Feeds page 330.

For detailed tolerance information, see page 329.