



AITiNX Coated

Double Margin, Solid Carbide, Coolant Fed, 142° Point, 3X Dia., 30° Helix (74409-6299)

Drill Size	Decimal Equiv	Flute Length	Drill Depth	OAL	Shank ø	AITiNX Coated Part #
11.20MM	.4409	55	40	102	12.0	RDX3316
11.30MM	.4449	55	40	102	12.0	RDX3317
11.40MM	.4488	55	40	102	12.0	RDX3318
11.50MM	.4527	55	40	102	12.0	RDX3319
11.55MM	.4547	55	40	102	12.0	RDX3320
11.60MM	.4567	55	40	102	12.0	RDX3321
11.70MM	.4606	55	40	102	12.0	RDX3322
11.80MM	.4646	55	40	102	12.0	RDX3323
11.90MM	.4685	55	40	102	12.0	RDX3324
15/32	.4688	2.165	1.575	4.016	1/2	RDX3325
12.00MM	.4724	55	40	102	12.0	RDX3326
12.10MM	.4764	60	43	107	14.0	RDX3327
31/64	.4844	2.362	1.693	4.213	1/2	RDX3328
12.50MM	.4921	60	43	107	14.0	RDX3329
1/2	.5000	2.362	1.693	4.213	1/2	RDX3330
12.80MM	.5039	60	43	107	14.0	RDX3331
12.83MM	.5051	60	43	107	14.0	RDX3332
12.90MM	.5079	60	43	107	14.0	RDX3333
13.00MM	.5118	60	43	107	14.0	RDX3334
33/64	.5156	2.362	1.693	4.213	9/16	RDX3335
13.20MM	.5197	60	43	107	14.0	RDX3336
17/32	.5312	2.362	1.693	4.213	9/16	RDX3337
13.50MM	.5315	60	43	107	14.0	RDX3338
13.70MM	.5394	60	43	107	14.0	RDX3339
35/64	.5469	2.362	1.693	4.213	9/16	RDX3340
14.00MM	.5512	60	43	107	14.0	RDX3341
9/16	.5625	2.559	1.772	4.528	9/16	RDX3342
14.50MM	.5709	65	45	115	16.0	RDX3343
14.70MM	.5787	65	45	115	16.0	RDX3344
14.75MM	.5807	65	45	115	16.0	RDX3345
15.00MM	.5905	65	45	115	16.0	RDX3346
19/32	.5938	2.559	1.772	4.528	5/8	RDX3347
15.30MM	.6024	65	45	115	16.0	RDX3348
15.50MM	.6102	65	45	115	16.0	RDX3349
15.70MM	.6181	65	45	115	16.0	RDX3350
5/8	.6250	2.559	1.772	4.528	5/8	RDX3351
16.00MM	.6299	65	45	115	16.0	RDX3352

For detailed tolerance information, see [page 329](#).



[Speeds & Feeds page 330](#).