

## Double Margin - 5XD



AlTiN Coated

### Double Margin, Solid Carbide, 142° Point, 5X Dia., 30° Helix (.1181-.2210)

Drill Size	Decimal Equiv	Flute Length	Drill Depth	OAL	Shank ø	AlTiN Coated Part #
3.00MM	.1181	28	23	66	3.0	<a href="#">RDX5000</a>
#31	.1200	1.102	.906	2.600	1/8	<a href="#">RDX5001</a>
3.10MM	.1220	28	23	66	4.0	<a href="#">RDX5002</a>
1/8	.1250	1.102	.906	2.600	1/8	<a href="#">RDX5003</a>
3.20MM	.1260	28	23	66	4.0	<a href="#">RDX5004</a>
#30	.1285	1.102	.906	2.600	1/64	<a href="#">RDX5005</a>
3.30MM	.1299	28	23	66	4.0	<a href="#">RDX5006</a>
3.40MM	.1339	28	23	66	4.0	<a href="#">RDX5007</a>
#29	.1360	1.102	.906	2.600	1/64	<a href="#">RDX5008</a>
3.50MM	.1378	28	23	66	4.0	<a href="#">RDX5009</a>
9/64	.1406	1.102	.906	2.600	1/64	<a href="#">RDX5010</a>
3.60MM	.1417	28	23	66	4.0	<a href="#">RDX5011</a>
3.70MM	.1457	28	23	66	4.0	<a href="#">RDX5012</a>
3.80MM	.1496	36	29	74	4.0	<a href="#">RDX5013</a>
#24	.1520	1.417	1.142	2.910	1/64	<a href="#">RDX5014</a>
3.90MM	.1535	36	29	74	4.0	<a href="#">RDX5015</a>
5/32	.1562	1.417	1.142	2.910	1/64	<a href="#">RDX5016</a>
4.00MM	.1575	36	29	74	4.0	<a href="#">RDX5017</a>
#21	.1590	1.417	1.142	2.910	3/16	<a href="#">RDX5018</a>
4.10MM	.1614	36	29	74	5.0	<a href="#">RDX5019</a>
4.20MM	.1654	36	29	74	5.0	<a href="#">RDX5020</a>
4.30MM	.1693	36	29	74	5.0	<a href="#">RDX5021</a>
11/64	.1719	1.417	1.142	2.910	3/16	<a href="#">RDX5022</a>
4.40MM	.1732	36	29	74	5.0	<a href="#">RDX5023</a>
4.50MM	.1772	36	29	74	5.0	<a href="#">RDX5024</a>
4.60MM	.1811	36	29	74	5.0	<a href="#">RDX5025</a>
4.70MM	.1850	36	29	74	5.0	<a href="#">RDX5026</a>
3/16	.1875	1.732	1.378	3.230	3/16	<a href="#">RDX5027</a>
4.80MM	.1890	44	35	82	5.0	<a href="#">RDX5028</a>
4.90MM	.1929	44	35	82	5.0	<a href="#">RDX5029</a>
5.00MM	.1968	44	35	82	5.0	<a href="#">RDX5030</a>
5.10MM	.2008	44	35	82	6.0	<a href="#">RDX5031</a>
13/64	.2031	1.732	1.378	3.230	1/4	<a href="#">RDX5032</a>
5.20MM	.2047	44	35	82	6.0	<a href="#">RDX5033</a>
5.30MM	.2087	44	35	82	6.0	<a href="#">RDX5034</a>
5.40MM	.2126	44	35	82	6.0	<a href="#">RDX5035</a>
5.50MM	.2165	44	35	82	6.0	<a href="#">RDX5036</a>
7/32	.2187	1.732	1.378	3.230	1/4	<a href="#">RDX5037</a>
5.60MM	.2205	44	35	82	6.0	<a href="#">RDX5038</a>
#2	.2210	1.732	1.378	3.230	1/4	<a href="#">RDX5039</a>



Speeds & Feeds page 329.

For detailed tolerance information, see page 329.