

Double Margin - 5XD



AITiNX Coated

Double Margin, Solid Carbide, Coolant Fed, 142° Point, 5X Dia., 30° Helix (3268-.4331)

Drill Size	Decimal Equiv	Flute Length	Drill Depth	OAL	Shank ø	AITiNX Coated Part #
8.30MM	.3268	61	49	103	10.0	RDX5276
21/64	.3281	2.402	1.929	4.060	3/8	RDX5277
8.40MM	.3307	61	49	103	10.0	RDX5278
Q	.3320	2.402	1.929	4.060	3/8	RDX5279
8.50MM	.3346	61	49	103	10.0	RDX5280
8.60MM	.3386	61	49	103	10.0	RDX5281
8.70MM	.3425	61	49	103	10.0	RDX5282
11/32	.3438	2.402	1.929	4.060	3/8	RDX5283
8.80MM	.3465	61	49	103	10.0	RDX5284
8.90MM	.3504	61	49	103	10.0	RDX5285
9.00MM	.3543	61	49	103	10.0	RDX5286
9.10MM	.3583	61	49	103	10.0	RDX5287
23/64	.3594	2.402	1.929	4.060	3/8	RDX5288
9.20MM	.3622	61	49	103	10.0	RDX5289
9.25MM	.3642	61	49	103	10.0	RDX5290
9.30MM	.3661	61	49	103	10.0	RDX5291
9.40MM	.3701	61	49	103	10.0	RDX5292
9.50MM	.3740	61	49	103	10.0	RDX5293
3/8	.3750	2.402	1.929	4.060	3/8	RDX5294
9.60MM	.3780	61	49	103	10.0	RDX5295
9.70MM	.3819	61	49	103	10.0	RDX5296
9.80MM	.3858	61	49	103	10.0	RDX5297
9.90MM	.3898	61	49	103	10.0	RDX5298
25/64	.3906	2.402	1.929	4.060	7/16	RDX5299
10.00MM	.3937	61	49	103	10.0	RDX5300
10.10MM	.3976	71	56	118	12.0	RDX5301
10.20MM	.4016	71	56	118	12.0	RDX5302
10.30MM	.4055	71	56	118	12.0	RDX5303
13/32	.4062	2.795	2.205	4.650	7/16	RDX5304
10.40MM	.4094	71	56	118	12.0	RDX5305
10.50MM	.4134	71	56	118	12.0	RDX5306
10.60MM	.4173	71	56	118	12.0	RDX5307
10.70MM	.4213	71	56	118	12.0	RDX5308
27/64	.4219	2.795	2.205	4.650	7/16	RDX5309
10.80MM	.4252	71	56	118	12.0	RDX5310
10.90MM	.4291	71	56	118	12.0	RDX5311
11.00MM	.4331	71	56	118	12.0	RDX5312



Carbide Drills



Speeds & Feeds page 330.

For detailed tolerance information, see page 329.