



AlTiN Coated

### Double Margin, Solid Carbide, Coolant Fed, 142° Point, 5X Dia., 30° Helix (4370-.6496)

Drill Size	Decimal Equiv	Flute Length	Drill Depth	OAL	Shank ø	AlTiN Coated Part #
11.10MM	.4370	71	56	118	12.0	<a href="#">RDX5313</a>
7/16	.4375	2.795	2.205	4.650	7/16	<a href="#">RDX5314</a>
11.20MM	.4409	71	56	118	12.0	<a href="#">RDX5315</a>
11.30MM	.4449	71	56	118	12.0	<a href="#">RDX5316</a>
11.40MM	.4488	71	56	118	12.0	<a href="#">RDX5317</a>
11.50MM	.4527	71	56	118	12.0	<a href="#">RDX5318</a>
11.60MM	.4567	71	56	118	12.0	<a href="#">RDX5319</a>
11.70MM	.4606	71	56	118	12.0	<a href="#">RDX5320</a>
11.80MM	.4646	71	56	118	12.0	<a href="#">RDX5321</a>
11.90MM	.4685	71	56	118	12.0	<a href="#">RDX5322</a>
15/32	.4688	2.795	2.205	4.650	1/2	<a href="#">RDX5323</a>
12.00MM	.4724	71	56	118	12.0	<a href="#">RDX5324</a>
12.10MM	.4764	77	60	124	14.0	<a href="#">RDX5325</a>
31/64	.4844	3.031	2.362	4.880	1/2	<a href="#">RDX5326</a>
12.50MM	.4921	77	60	124	14.0	<a href="#">RDX5327</a>
1/2	.5000	3.031	2.362	4.880	1/2	<a href="#">RDX5328</a>
12.80MM	.5039	77	60	124	14.0	<a href="#">RDX5329</a>
12.83MM	.5051	77	60	124	14.0	<a href="#">RDX5330</a>
12.90MM	.5079	77	60	124	14.0	<a href="#">RDX5331</a>
13.00MM	.5118	77	60	124	14.0	<a href="#">RDX5332</a>
33/64	.5156	3.031	2.362	4.880	9/16	<a href="#">RDX5333</a>
17/32	.5312	3.031	2.362	4.880	9/16	<a href="#">RDX5334</a>
13.50MM	.5315	77	60	124	14.0	<a href="#">RDX5335</a>
13.70MM	.5394	77	60	124	14.0	<a href="#">RDX5336</a>
35/64	.5469	3.031	2.362	4.880	9/16	<a href="#">RDX5337</a>
14.00MM	.5512	77	60	124	14.0	<a href="#">RDX5338</a>
9/16	.5625	3.268	2.480	5.240	9/16	<a href="#">RDX5339</a>
14.50MM	.5709	83	63	133	16.0	<a href="#">RDX5340</a>
14.70MM	.5787	83	63	133	16.0	<a href="#">RDX5341</a>
15.00MM	.5905	83	63	133	16.0	<a href="#">RDX5342</a>
19/32	.5938	3.268	2.480	5.240	5/8	<a href="#">RDX5343</a>
15.30MM	.6024	83	63	133	16.0	<a href="#">RDX5344</a>
15.50MM	.6102	83	63	133	16.0	<a href="#">RDX5345</a>
15.70MM	.6181	83	63	133	16.0	<a href="#">RDX5346</a>
5/8	.6250	3.268	2.480	5.240	5/8	<a href="#">RDX5347</a>
16.00MM	.6299	83	63	133	16.0	<a href="#">RDX5348</a>
16.08MM	.6331	93	71	143	18.0	<a href="#">RDX5349</a>
16.30MM	.6417	93	71	143	18.0	<a href="#">RDX5350</a>
16.50MM	.6496	93	71	143	18.0	<a href="#">RDX5351</a>



For detailed tolerance information, see [page 329](#).



[Speeds & Feeds page 330](#).