

## Aluminum & Non-Ferrous



DLC Coated

### Aluminum & Non-Ferrous, 5-Flute, Square & Corner Radius, 35° Helix

Cutter ø	Decimal Equiv	Flute Length	OAL	Corner Radius	Shank ø	DLC Coated Part #
3/4	.7500	2-1/4	5	—	3/4	<a href="#">REA5095</a>
3/4	.7500	2-1/4	5	.030	3/4	<a href="#">REA5097</a>
3/4	.7500	2-1/4	5	.060	3/4	<a href="#">REA5098</a>
3/4	.7500	2-1/4	5	.090	3/4	<a href="#">REA5099</a>
3/4	.7500	2-1/4	5	.125	3/4	<a href="#">REA5100</a>
3/4	.7500	2-1/4	5	.187	3/4	<a href="#">REA5101</a>
3/4	.7500	2-1/4	5	.250	3/4	<a href="#">REA5102</a>
3/4	.7500	2-5/8	5	—	3/4	<a href="#">REA5103</a>
3/4	.7500	2-5/8	5	.030	3/4	<a href="#">REA5105</a>
3/4	.7500	2-5/8	5	.060	3/4	<a href="#">REA5106</a>
3/4	.7500	2-5/8	5	.125	3/4	<a href="#">REA5108</a>
3/4	.7500	3	6	—	3/4	<a href="#">REA5111</a>
3/4	.7500	3	6	.030	3/4	<a href="#">REA5113</a>
3/4	.7500	3	6	.060	3/4	<a href="#">REA5114</a>
3/4	.7500	3	6	.090	3/4	<a href="#">REA5115</a>
3/4	.7500	3	6	.125	3/4	<a href="#">REA5116</a>
3/4	.7500	3	6	.250	3/4	<a href="#">REA5118</a>
1	1.0000	2	5	—	1	<a href="#">REA5119</a>
1	1.0000	2	5	.030	1	<a href="#">REA5121</a>
1	1.0000	2	5	.125	1	<a href="#">REA5124</a>
1	1.0000	2	5	.187	1	<a href="#">REA5125</a>
1	1.0000	2	5	.250	1	<a href="#">REA5126</a>
1	1.0000	3	6	—	1	<a href="#">REA5127</a>
1	1.0000	3	6	.030	1	<a href="#">REA5129</a>
1	1.0000	3	6	.125	1	<a href="#">REA5132</a>
1	1.0000	3	6	.187	1	<a href="#">REA5133</a>
1	1.0000	3	6	.250	1	<a href="#">REA5134</a>
1	1.0000	4	7	—	1	<a href="#">REA5135</a>
1	1.0000	4	7	.030	1	<a href="#">REA5137</a>
1	1.0000	4	7	.125	1	<a href="#">REA5140</a>
1	1.0000	4	7	.250	1	<a href="#">REA5142</a>

Carbide Endmills



Speeds & Feeds page 188.  
Tool application data pages 208-212.

Tolerances	Diameter	Shank	Radius
Fractional	-0.0001, -0.0004	h6	+0.0015, -0.0015

For specific shank tolerance information please see page 200.