



Uncoated

**Aluminum & Non-Ferrous, Solid Carbide, 3-Flute, Parabolic, 150° Point, 5X Dia., 30° Helix (5000-7500)**

Drill Size	Decimal Equiv	Flute Length	Drill Depth	OAL	Shank ø	Uncoated Part #
1/2	.5000	3	2-1/4	4-3/4	1/2	<a href="#">RDH3117</a>
13.00MM	.5118	77	60	124	14	<a href="#">RDH3118</a>
33/64	.5156	3-1/4	2-7/16	5	33/64	<a href="#">RDH3119</a>
17/32	.5312	3-1/4	2-7/16	5	17/32	<a href="#">RDH3120</a>
13.50MM	.5315	77	60	124	14	<a href="#">RDH3121</a>
35/64	.5469	3-1/4	2-7/16	5	35/64	<a href="#">RDH3122</a>
14.00MM	.5512	77	60	124	14	<a href="#">RDH3123</a>
9/16	.5625	3-1/4	2-7/16	5	9/16	<a href="#">RDH3124</a>
14.50MM	.5709	83	63	133	16	<a href="#">RDH3125</a>
15.00MM	.5906	83	63	133	16	<a href="#">RDH3126</a>
15.50MM	.6102	83	63	133	16	<a href="#">RDH3127</a>
15.80MM	.6220	83	63	133	16	<a href="#">RDH3128</a>
5/8	.6250	3-1/2	2-5/8	5-1/4	5/8	<a href="#">RDH3129</a>
16.00MM	.6299	83	63	133	16	<a href="#">RDH3130</a>
21/32	.6562	3-5/8	2-23/32	5-1/2	21/32	<a href="#">RDH3131</a>
11/16	.6875	3-5/8	2-23/32	5-1/2	11/16	<a href="#">RDH3132</a>
3/4	.7500	3-7/8	2-29/32	5-3/4	3/4	<a href="#">RDH3133</a>

Carbide Drills

For detailed tolerance information, see page 337.



Speeds & Feeds page 337.