

## Jobber Length



Oxide



Bright



TiN Coated

### HSS, Jobber Length, 118° Point (.0394-.0860)

Drill Size	Decimal Equiv	Flute Length	OAL	Pkg Qty	Oxide Part #	Bright Part #	TiN Coated Part #
1.00MM	.0394	18	41	12	<a href="#">RD46300</a>	—	—
#60	.0400	11/16	1-5/8	12	<a href="#">RD40060</a>	<a href="#">RD40360</a>	<a href="#">RD41260</a>
#59	.0410	11/16	1-5/8	12	<a href="#">RD40059</a>	<a href="#">RD40359</a>	<a href="#">RD41259</a>
1.05MM	.0413	18	41	12	<a href="#">RD46305</a>	—	—
#58	.0420	11/16	1-5/8	12	<a href="#">RD40058</a>	<a href="#">RD40358</a>	<a href="#">RD41258</a>
#57	.0430	3/4	1-3/4	12	<a href="#">RD40057</a>	<a href="#">RD40357</a>	<a href="#">RD41257</a>
1.10MM	.0433	19	44	12	<a href="#">RD46310</a>	—	—
1.15MM	.0453	19	44	12	<a href="#">RD46315</a>	—	—
#56	.0465	3/4	1-3/4	12	<a href="#">RD40056</a>	<a href="#">RD40356</a>	<a href="#">RD41256</a>
1.20MM	.0472	22	48	12	<a href="#">RD46320</a>	—	—
1.25MM	.0492	22	48	12	<a href="#">RD46325</a>	—	—
1.30MM	.0512	22	48	12	<a href="#">RD46330</a>	—	—
#55	.0520	7/8	1-7/8	12	<a href="#">RD40055</a>	<a href="#">RD40355</a>	<a href="#">RD41255</a>
#54	.0550	7/8	1-7/8	12	<a href="#">RD40054</a>	<a href="#">RD40354</a>	<a href="#">RD41254</a>
1.40MM	.0551	22	48	12	<a href="#">RD46340</a>	—	—
1.50MM	.0591	22	48	12	<a href="#">RD46350</a>	—	—
#53	.0595	7/8	1-7/8	12	<a href="#">RD40053</a>	<a href="#">RD40353</a>	<a href="#">RD41253</a>
1/16	.0625	7/8	1-7/8	12	<a href="#">RD40204</a>	<a href="#">RD40504</a>	<a href="#">RD41404</a>
1.60MM	.0630	22	48	12	<a href="#">RD46360</a>	—	—
#52	.0635	7/8	1-7/8	12	<a href="#">RD40052</a>	<a href="#">RD40352</a>	<a href="#">RD41252</a>
1.70MM	.0669	25	51	12	<a href="#">RD46370</a>	—	—
#51	.0670	1	2	12	<a href="#">RD40051</a>	<a href="#">RD40351</a>	<a href="#">RD41251</a>
#50	.0700	1	2	12	<a href="#">RD40050</a>	<a href="#">RD40350</a>	<a href="#">RD41250</a>
1.80MM	.0709	25	51	12	<a href="#">RD46380</a>	—	—
#49	.0730	1	2	12	<a href="#">RD40049</a>	<a href="#">RD40349</a>	<a href="#">RD41249</a>
1.90MM	.0748	25	51	12	<a href="#">RD46390</a>	—	—
#48	.0760	1	2	12	<a href="#">RD40048</a>	<a href="#">RD40348</a>	<a href="#">RD41248</a>
5/64	.0781	1	2	12	<a href="#">RD40205</a>	<a href="#">RD40505</a>	<a href="#">RD41405</a>
#47	.0785	1	2	12	<a href="#">RD40047</a>	<a href="#">RD40347</a>	<a href="#">RD41247</a>
2.00MM	.0787	25	51	12	<a href="#">RD46400</a>	—	—
#46	.0810	1-1/8	2-1/8	12	<a href="#">RD40046</a>	<a href="#">RD40346</a>	<a href="#">RD41246</a>
#45	.0820	1-1/8	2-1/8	12	<a href="#">RD40045</a>	<a href="#">RD40345</a>	<a href="#">RD41245</a>
#44	.0860	1-1/8	2-1/8	12	<a href="#">RD40044</a>	<a href="#">RD40344</a>	<a href="#">RD41244</a>



Speeds & Feeds page 340.