



DLC Coated

Aluminum & Non-Ferrous, 5-Flute, Square & Corner Radius, Neck Relief, 35° Helix

Cutter ø	Decimal Equiv	Flute Length	OAL	Length Below Shank	Neck ø	Corner Radius	Shank ø	DLC Coated Part #
1/4	.2500	3/8	2-1/2	7/8	.235	—	1/4	REA5300
1/4	.2500	3/8	2-1/2	7/8	.235	.015	1/4	REA5301
1/4	.2500	3/8	2-1/2	7/8	.235	.030	1/4	REA5302
1/4	.2500	3/8	2-1/2	7/8	.235	.060	1/4	REA5303
1/4	.2500	3/8	3	1-3/8	.235	—	1/4	REA5304
1/4	.2500	3/8	3	1-3/8	.235	.015	1/4	REA5305
1/4	.2500	3/8	3	1-3/8	.235	.030	1/4	REA5306
1/4	.2500	3/8	3	1-3/8	.235	.060	1/4	REA5307
1/4	.2500	3/8	4	2-1/4	.235	—	1/4	REA5308
1/4	.2500	3/8	4	2-1/4	.235	.015	1/4	REA5309
1/4	.2500	3/8	4	2-1/4	.235	.030	1/4	REA5310
3/8	.3750	9/16	2-1/2	1-1/16	.355	—	3/8	REA5312
3/8	.3750	9/16	2-1/2	1-1/16	.355	.015	3/8	REA5313
3/8	.3750	9/16	2-1/2	1-1/16	.355	.030	3/8	REA5314
3/8	.3750	9/16	2-1/2	1-1/16	.355	.060	3/8	REA5315
3/8	.3750	9/16	2-1/2	1-1/16	.355	.090	3/8	REA5316
3/8	.3750	9/16	3	1-1/8	.355	—	3/8	REA5317
3/8	.3750	9/16	3	1-1/8	.355	.015	3/8	REA5318
3/8	.3750	9/16	3	1-1/8	.355	.030	3/8	REA5319
3/8	.3750	9/16	3	1-1/8	.355	.060	3/8	REA5320
3/8	.3750	9/16	3	1-1/8	.355	.090	3/8	REA5321
3/8	.3750	9/16	4	2-3/16	.355	—	3/8	REA5322
3/8	.3750	9/16	4	2-3/16	.355	.015	3/8	REA5323
3/8	.3750	9/16	4	2-3/16	.355	.030	3/8	REA5324
1/2	.5000	3/4	3	1-1/4	.475	—	1/2	REA5327
1/2	.5000	3/4	3	1-1/4	.475	.015	1/2	REA5328
1/2	.5000	3/4	3	1-1/4	.475	.030	1/2	REA5329
1/2	.5000	3/4	3	1-1/4	.475	.060	1/2	REA5330
1/2	.5000	3/4	3	1-1/4	.475	.090	1/2	REA5331
1/2	.5000	3/4	3	1-1/4	.475	.125	1/2	REA5332
1/2	.5000	3/4	4	2-1/8	.475	—	1/2	REA5333
1/2	.5000	3/4	4	2-1/8	.475	.015	1/2	REA5334
1/2	.5000	3/4	4	2-1/8	.475	.030	1/2	REA5335
1/2	.5000	3/4	4	2-1/8	.475	.060	1/2	REA5336
1/2	.5000	3/4	4	2-1/8	.475	.090	1/2	REA5337
1/2	.5000	3/4	4	2-1/8	.475	.125	1/2	REA5338
1/2	.5000	3/4	5	3-1/8	.475	—	1/2	REA5339
1/2	.5000	3/4	5	3-1/8	.475	.015	1/2	REA5340
1/2	.5000	3/4	5	3-1/8	.475	.030	1/2	REA5341



Speeds & Feeds page 188.
Tool application data pages 208-212.

Tolerances	Diameter	Shank	Radius
Fractional	-0.0001, -0.0004	h6	+0.0015, -0.0015

For specific shank tolerance information please see page 200.