



AICrN Coated

### Variable Helix, 3-Flute, Square & Corner Radius, Metric

Cutter ø	Decimal Equiv	Flute Length	OAL	Corner Radius	Shank ø	AICrN Coated Part #
6MM	.2362	18	63.5	.5	6	<a href="#">REM2076</a>
6MM	.2362	18	63.5	1	6	<a href="#">REM2077</a>
6MM	.2362	18	63.5	1.5	6	<a href="#">REM2078</a>
6MM	.2362	18	63.5	2	6	<a href="#">REM2079</a>
8MM	.3150	12	63.5	—	8	<a href="#">REM2080</a>
8MM	.3150	12	63.5	.2	8	<a href="#">REM2081</a>
8MM	.3150	12	63.5	.3	8	<a href="#">REM2082</a>
8MM	.3150	12	63.5	.5	8	<a href="#">REM2083</a>
8MM	.3150	12	63.5	1	8	<a href="#">REM2084</a>
8MM	.3150	12	63.5	1.5	8	<a href="#">REM2085</a>
8MM	.3150	12	63.5	2	8	<a href="#">REM2086</a>
8MM	.3150	24	63.5	—	8	<a href="#">REM2087</a>
8MM	.3150	24	63.5	.2	8	<a href="#">REM2088</a>
8MM	.3150	24	63.5	.3	8	<a href="#">REM2089</a>
8MM	.3150	24	63.5	.5	8	<a href="#">REM2090</a>
8MM	.3150	24	63.5	1	8	<a href="#">REM2091</a>
8MM	.3150	24	63.5	1.5	8	<a href="#">REM2092</a>
8MM	.3150	24	63.5	2	8	<a href="#">REM2093</a>

Tolerances	Diameter	Shank	Radius
Metric	+0.000, -0.020	+0.000, -0.008	+0.050, -0.050



Speeds & Feeds page 189.