

Micro 3-Flute - Variable Helix



AlCrN Coated

Variable Helix, 3-Flute, Extended Reach, Square & Corner Radius

Cutter ϕ	Decimal Equiv	Flute Length	Reach Length	OAL	Corner Radius	Shank ϕ	AlCrN Coated Part #
1/32	.0312	.063	.155	2-1/2	—	1/4	REM1044
1/32	.0312	.094	.155	2-1/2	.006	1/4	REM1045
3/64	.0469	.094	.230	2-1/2	—	1/4	REM1046
3/64	.0469	.141	.230	2-1/2	.010	1/4	REM1047
1/16	.0625	.140	.312	2-1/2	—	1/4	REM1048
1/16	.0625	.188	.312	2-1/2	.010	1/4	REM1049
5/64	.0781	.140	.390	2-1/2	—	1/4	REM1050
5/64	.0781	.234	.390	2-1/2	.010	1/4	REM1051
3/32	.0938	.188	.465	2-1/2	—	1/4	REM1052
3/32	.0938	.375	.465	2-1/2	.010	1/4	REM1053
7/64	.1094	.188	.545	2-1/2	—	1/4	REM1054
7/64	.1094	.438	.545	2-1/2	.010	1/4	REM1055
1/8	.1250	.250	.625	2-1/2	—	1/4	REM1056
1/8	.1250	.500	.625	2-1/2	.015	1/4	REM1057
5/32	.1562	.375	.781	2-1/2	—	1/4	REM1058
5/32	.1562	.563	.781	2-1/2	.015	1/4	REM1059
3/16	.1875	.375	.938	2-1/2	—	1/4	REM1060
3/16	.1875	.625	.938	2-1/2	.015	1/4	REM1061
7/32	.2188	.375	1.093	2-1/2	—	1/4	REM1062
7/32	.2188	.625	1.093	2-1/2	.015	1/4	REM1063
1/4	.2500	.500	1.250	2-1/2	—	1/4	REM1064
1/4	.2500	.750	1.250	2-1/2	.015	1/4	REM1065

Carbide Endmills



Speeds & Feeds page 189.

Tolerances	Diameter	Shank	Radius
Fractional	+0.000, -0.0008	+0.000, -0.0003	+0.002, -0.002