General Purpose - Taps

Fast Spiral



HSS, Fast Spiral Fluted Bottoming Taps for Non-Ferrous Materials, 52° Helix 📚

Size & Pitch	GH Limit	# of Flutes	Pkg Qty	Uncoated Part #
3-48	H2	2	1	RT34701
3-56	H2	2	1	RT34703
0.00	112	-		1110-1100
4.40	110	0	4	DT0 4705
4-40	H2	2	1	<u>RT34705</u>
4-48	H2	2	1	<u>RT34707</u>
5-40	H3	2	1	RT34709
5-44	H3	2	1	RT34711
• • • •	110			<u></u>
0.00	110	0		DT0 (740
6-32	H3	2	1	<u>RT34713</u>
6-40	H3	2	1	<u>RT34715</u>
8-32	H3	3	1	RT34717
8-36	H3	3	1	RT34719
0.00	110		•	1104110
40.04	110	0	4	DT0 (70)
10-24	H3	3	1	<u>RT34721</u>
10-32	H3	3	1	<u>RT34723</u>
12-24	H3	3	1	RT34725
12-28	H3	3	1	RT34727
1/4-20	H3	3	1	DT24720
1/4-20	пэ	3	1	<u>RT34729</u>
1/4-28	H3	3	1	<u>RT34731</u>
5/16-18	H3	3	1	<u>RT34733</u>
5/16-24	H3	3	1	<u>RT34735</u>
3/8-16	H3	3	1	RT34737
5/0-10	115	5	1	1104/01
0/0.04				
3/8-24	H3	3	1	<u>RT34739</u>
7/16-14	H3	3	1	<u>RT34741</u>
7/16-20	H3	3	1	<u>RT34743</u>
		-		<u></u>

