
CAT50 & Straight Shank ER40 Collet Chucks

(Balanced to G2.5@15,000 RPM)



- · Increased flexibility for milling, drilling, and reaming
- Flush precision collet nut, grips tool close to cutting edge for accuracy and rigidity
- Concentric to .0002" TIR puts tool precisely on spindle center line
- AT3 or better shank taper allows for accurate, rigid toolholder-tospindle mount
- · Wide range collets reduce collet and toolholder inventories
- Fully ground flange and V-groove is easy on tool changers for less spindle and changer maintenance
- Through spindle coolant standard
- ER40 Collets found on pages 610-612.



CAT50 ER40 Collet Chucks							
Capacity	Taper	Α	Gage Length (B)	D	L	Max. Nosepiece Torque	Part #
.086-1.023	CAT50	2.48	4.00	4.0	1.38	72 ft lbs	RC5ER404000
.086-1.023	CAT50	2.48	6.00	5.0	1.38	72 ft lbs	RC5ER406000

ER40 Straight Shank Collet Extension							
Α	В	D	L	Photo	Dimensions	Part #	
2.48	6.0	1.25	3.50		A A	RSSER40600	

ER40 Parts & Accessories							
Description	Photo	Dimensions	Part #				
ER40 Replacement Nosepiece	0	2.48	RER40NPA				
ER40 Collet Wrench [†]		4.00	RER40W				
ER40 Stop Screw		trehane Sed	RER40SS				
ER40 Stop Screw Coolant Thru		L.H. Goolaat Threads Passage (MIS x 1.5)	RER40SSC				

[†]Required for assembly.