


Facemill

CAT50 Facemill Holders



- Pilot diameter is sized for precision fit with cutter
- Face perpendicular to center line within .0002"
- Removable/replaceable drive keys are standard
- Fine thread locking screw is included
- AT3 or better shank taper allows for accurate, rigid toolholder-to-spindle mount
- Less tool wear and replacement means less scrap
- Fully ground flange and V-groove is easy on tool changers for less spindle and changer maintenance



Toolholders

CAT50 Facemill Holders

Taper	Size A	Gage Length (B)	C	L	Part #
CAT50	1/2	1.50	1.44	1.38	RC5SM05001500
CAT50	1/2	3.50	1.44	1.38	RC5SM05003500
CAT50	1/2	5.50	1.44	1.38	RC5SM05005500
CAT50	3/4	1.50	1.69	1.38	RC5SM07501500
CAT50	3/4	3.50	1.69	1.38	RC5SM07503500
CAT50	3/4	5.50	1.69	1.38	RC5SM07505500
CAT50	1	2.00	2.19	1.38	RC5SM10002000
CAT50	1	4.00	2.19	1.38	RC5SM10004000
CAT50	1	6.00	2.19	1.38	RC5SM10006000
CAT50	1-1/4	1.50	2.75	1.38	RC5SM12501500
CAT50	1-1/4	3.50	2.75	1.38	RC5SM12503500
CAT50	1-1/4	5.50	2.75	1.38	RC5SM12505500
CAT50	1-1/2	2.50	3.81	1.38	RC5SM15002500
CAT50	1-1/2	4.00	3.81	1.38	RC5SM15004000
CAT50	1-1/2	6.00	3.81	1.38	RC5SM15006000
CAT50	2	3.00	4.88	1.38	RC5SM20003000
CAT50	2	4.00	4.88	1.38	RC5SM20004000
CAT50	2	6.00	4.88	1.38	RC5SM20006000
CAT50	2	2.40	4.88	1.38	RC5SM25002400
CAT50	2	4.00	4.88	1.38	RC5SM25004000

Facemill Holder Replacement Lock Screws

Holder Size	Size A	B	C	D	Photo	Dimensions	Part #
1/2	.625	1/4-28	.50	.34			RSMLS0500
3/4	.875	3/8-24	.63	.37			RSMLS0750
1	1.188	1/2-20	.81	.37			RSMLS1000
1-1/4	1.500	5/8-18	.94	.50			RSMLS1250
1-1/2	1.875	3/4-16	1.13	.50			RSMLS1500
2	2.500	1.0-14	1.31	.50			RSMLS2000
2-1/2	3.125	1.0-14	1.50	.50			RSMLS2500

