



AICrNX Coated

### 9-Flute Finishers, Chip Control, Corner Radius, 36° Helix

Cutter ø	Decimal Equiv	Flute Length	OAL	Corner Radius	Shank ø	AICrNX Coated Part #
1/2	.500	1	3	.030	1/2	<a href="#">RFZ09200</a>
1/2	.500	1-1/4	3-1/4	.030	1/2	<a href="#">RFZ09201</a>
1/2	.500	1-1/2	3-1/2	.030	1/2	<a href="#">RFZ09202</a>
1/2	.500	1-1/2	3-1/2	.060	1/2	<a href="#">RFZ09203</a>
1/2	.500	1-3/4	4	.030	1/2	<a href="#">RFZ09204</a>
1/2	.500	1-3/4	4	.060	1/2	<a href="#">RFZ09205</a>
5/8	.625	1-1/4	3-1/2	.030	5/8	<a href="#">RFZ09206</a>
5/8	.625	1-9/16	4	.030	5/8	<a href="#">RFZ09207</a>
5/8	.625	1-9/16	4	.060	5/8	<a href="#">RFZ09208</a>
5/8	.625	1-7/8	4	.030	5/8	<a href="#">RFZ09209</a>
5/8	.625	1-7/8	4	.060	5/8	<a href="#">RFZ09210</a>
5/8	.625	2-3/16	4-1/2	.030	5/8	<a href="#">RFZ09211</a>
5/8	.625	2-3/16	4-1/2	.060	5/8	<a href="#">RFZ09212</a>
3/4	.750	1-1/2	4	.030	3/4	<a href="#">RFZ09213</a>
3/4	.750	1-1/2	4	.060	3/4	<a href="#">RFZ09214</a>
3/4	.750	1-1/2	4	.125	3/4	<a href="#">RFZ09215</a>
3/4	.750	1-7/8	4-1/2	.030	3/4	<a href="#">RFZ09216</a>
3/4	.750	1-7/8	4-1/2	.060	3/4	<a href="#">RFZ09217</a>
3/4	.750	1-7/8	4-1/2	.125	3/4	<a href="#">RFZ09218</a>
3/4	.750	2-1/4	5	.030	3/4	<a href="#">RFZ09219</a>
3/4	.750	2-1/4	5	.060	3/4	<a href="#">RFZ09220</a>
3/4	.750	2-1/4	5	.125	3/4	<a href="#">RFZ09221</a>
3/4	.750	2-5/8	5	.030	3/4	<a href="#">RFZ09222</a>
3/4	.750	2-5/8	5	.060	3/4	<a href="#">RFZ09223</a>
3/4	.750	2-5/8	5	.125	3/4	<a href="#">RFZ09224</a>
1	1.000	2	5	.030	1	<a href="#">RFZ09225</a>
1	1.000	2	5	.060	1	<a href="#">RFZ09226</a>
1	1.000	2	5	.125	1	<a href="#">RFZ09227</a>
1	1.000	2-1/2	5-1/2	.030	1	<a href="#">RFZ09228</a>
1	1.000	2-1/2	5-1/2	.060	1	<a href="#">RFZ09229</a>
1	1.000	2-1/2	5-1/2	.125	1	<a href="#">RFZ09230</a>
1	1.000	3	6	.030	1	<a href="#">RFZ09231</a>
1	1.000	3	6	.060	1	<a href="#">RFZ09232</a>
1	1.000	3	6	.125	1	<a href="#">RFZ09233</a>
1	1.000	3-1/2	6-1/2	.030	1	<a href="#">RFZ09234</a>
1	1.000	3-1/2	6-1/2	.060	1	<a href="#">RFZ09235</a>
1	1.000	3-1/2	6-1/2	.125	1	<a href="#">RFZ09236</a>

Tolerances	Diameter	Shank	Radius
Fractional	+0.000, -0.002	h6	+0.0015, -0.0015

For specific shank tolerance information please see [page 200](#).



[Speeds & Feeds page 205.](#)

[Tool application data pages 208-212.](#)