2 Flute: Square & Ball End
4 Flute: Square & Ball End



Diamond 1, 1B, 3, 3B Fractional		Ae x DC	Ap x DC	Vc (sfm)		DC • in 1/8	1/4	5/16	3/8	1/2
GRAPHITE Ultrafine, Superfine	Profile	≤ 0.25	≤ 1.5	720	RPM	22003	11002	8801	7334	5501
				(576-864)	Fz	0.0009	0.0023	0.0036	0.0043	0.0058
					Feed 2 flutes (ipm)	38.3	50.6	63.4	63.1	63.8
					Feed 4 flutes (ipm)	76.6	101.2	126.7	126.2	127.6
	Slot	≤ 1	≤ 1	580	RPM	17725	8862	7090	5908	4431
				(464-696)	Fz	0.0075	0.0020	0.0031	0.0038	0.0050
					Feed 2 flutes (ipm)	265.9	35.4	44.0	44.9	44.3
					Feed 4 flutes (ipm)	531.7	70.9	87.9	89.8	88.6
COMPOSITES FRP, CFRP, GRP	Profile	≤ 0.25	≤ 1.5	385	RPM	11766	5883	4706	3922	2941
				(308-462)	Fz	0.0005	0.0014	0.0022	0.0026	0.0035
					Feed 2 flutes (ipm)	12.2	16.5	20.7	20.4	20.6
					Feed 4 flutes (ipm)	24.5	32.9	41.4	40.8	41.2
	Slot	≤ 1	≤ 1	350	RPM	10696	5348	4278	3565	2674
				(280-420)	Fz	0.0005	0.0012	0.0019	0.0023	0.0030
					Feed 2 flutes (ipm)	9.6	12.8	16.3	16.4	16.0
					Feed 3 flutes (ipm)	19.3	25.7	32.5	32.8	32.1
PLASTICS Polycarbonate, PVC, Polypropylene	Profile	≤ 0.25	≤ 1.5	1200	RPM	36672	18336	14669	12224	9168
				(960-1440)	Fz	0.0009	0.0023	0.0036	0.0043	0.0058
					Feed 2 flutes (ipm)	63.8	84.3	105.6	105.1	106.3
					Feed 4 flutes (ipm)	127.6	168.7	211.2	210.3	212.7
	Slot	≤ 1	≤ 1	960	RPM	29338	14669	11735	9779	7334
				(768-1152)	Fz	0.0008	0.0020	0.0031	0.0038	0.0050
					Feed 2 flutes (ipm)	44.0	58.7	72.8	74.3	73.3
					Feed 3 flutes (ipm)	88.0	117.4	145.5	148.6	146.7

rpm = (Vc x 3.82) / DC
ipm = Fz x number of flutes x rpm
finish cuts typically require reduced feed and cut depths (.02 x D maximum)
refer to the SGS Tool Wizard® for complete technical information (www.kyocera-sgstool.com)

2 Flute: Square, Double, Stub, Long, Ball, Corner Radius
3 Flute: Square, Ball, Tapered
4 Flute: Square, Double, Stub, Ball, Corner Radius
Tapered: Square, Radius



	Series 1, 3, 5, 14, 15, 16, 17, 23, 24, 59 Fractional	Hardness		Flutes	Ae x DC	Ap x DC	Vc (sfm)		DC • in 1/64	1/32	1/16	1/8	1/4	3/8	1/2	3/4	1
P	CARBON STEELS 1018, 1040, 1080, 1090, 10L50, 1140, 1212, 12L15, 1525, 1536	≤ 175 Bhn or ≤ 7 HRc	Profile				460	RPM	112461	56230	28115	14058	7029	4686	3514	2343	1757
								Fz	0.00003	0.00006	0.00013	0.0003	0.0008	0.0015	0.0020	0.0024	0.0028
				2	≤ 0.50	≤ 1.5	(368-552)	Feed (ipm)	6.7	6.7	7.3	8.4	11.2	14.1	14.1	11.2	9.8
				3	≤ 0.25	≤ 1.5			10.1	10.1	11.0	12.7	16.9	21.1	21.1	16.9	14.8
				4	≤ 0.25	≤ 1.5			13.5	13.5	14.6	16.9	22.5	28.1	28.1	22.5	19.7
			Slot				335	RPM	81901	40950	20475	10238	5119	3413	2559	1706	1280
								Fz	0.00003	0.00006	0.00013	0.0003	0.0008	0.0015	0.0020	0.0024	0.0028
				2	1	≤ 1	(268-402)	Feed (ipm)	4.9	4.9	5.3	6.1	8.2	10.2	10.2	8.2	7.2
				3	1	≤ 0.5			7.4	7.4	8.0	9.2	12.3	15.4	15.4	12.3	10.7
				4	1	≤ 0.4			9.8	9.8	10.6	12.3	16.4	20.5	20.5	16.4	14.3
	ALLOY STEELS 4140, 4150, 4320, 5120, 5150, 8630, 86L20, 50100	≤ 275 Bhn or ≤ 28 HRc	Profile				335	RPM	81901	40950	20475	10238	5119	3413	2559	1706	1280
								Fz	0.00002	0.00005	0.00009	0.0002	0.0006	0.0011	0.0015	0.0018	0.0021
				2	≤ 0.50	≤ 1.5	(268-402)	Feed (ipm)	3.3	4.1	3.7	4.1	6.1	7.5	7.7	6.1	5.4
				3	≤ 0.25	≤ 1.5			4.9	6.1	5.5	6.1	9.2	11.3	11.5	9.2	8.1
				4	≤ 0.25	≤ 1.5			6.6	8.2	7.4	8.2	12.3	15.0	15.4	12.3	10.7
			Slot				245	RPM	59898	29949	14974	7487	3744	2496	1872	1248	936
								Fz	0.00002	0.00005	0.00009	0.0002	0.0006	0.0011	0.0015	0.0018	0.0021
				2	1	≤ 1	(196-294)	Feed (ipm)	2.4	3.0	2.7	3.0	4.5	5.5	5.6	4.5	3.9
				3	1	≤ 0.5			3.6	4.5	4.0	4.5	6.7	8.2	8.4	6.7	5.9
				4	1	≤ 0.4			4.8	6.0	5.4	6.0	9.0	11.0	11.2	9.0	7.9
M	STAINLESS STEELS (FREE MACHINING) 303, 416, 420F, 430F 440F	≤ 275 Bhn or ≤ 28 HRc	Profile				370	RPM	90458	45229	22614	11307	5654	3769	2827	1885	1413
								Fz	0.00002	0.00005	0.00009	0.0002	0.0006	0.0011	0.0015	0.0018	0.0021
				2	≤ 0.50	≤ 1.5	(296-444)	Feed (ipm)	3.6	4.5	4.1	4.5	6.8	8.3	8.5	6.8	5.9
				3	≤ 0.25	≤ 1.5			5.4	6.8	6.1	6.8	10.2	12.4	12.7	10.2	8.9
				4	≤ 0.25	≤ 1.5			7.2	9.0	8.1	9.0	13.6	16.6	17.0	13.6	11.9
			Slot				270	RPM	66010	33005	16502	8251	4126	2750	2063	1375	1031
								Fz	0.00002	0.00005	0.00009	0.0002	0.0006	0.0011	0.0015	0.0018	0.0021
				2	1	≤ 1	(216-324)	Feed (ipm)	2.6	3.3	3.0	3.3	5.0	6.1	6.2	5.0	4.3
				3	1	≤ 0.5			4.0	5.0	4.5	5.0	7.4	9.1	9.3	7.4	6.5
				4	1	≤ 0.4			5.3	6.6	5.9	6.6	9.9	12.1	12.4	9.9	8.7
	STAINLESS STEELS (DIFFICULT) 304, 304L, 316, 316L, 17-4 PH, 15-5, 13-4, Custom 450	≤ 275 Bhn or ≤ 28 HRc	Profile				255	RPM	62342	31171	15586	7793	3896	2598	1948	1299	974
								Fz	0.00002	0.00004	0.00008	0.0002	0.0005	0.0009	0.0012	0.0014	0.0017
				2	≤ 0.50	≤ 1.5	(204-306)	Feed (ipm)	2.5	2.5	2.5	2.6	3.9	4.7	4.7	3.6	3.3
				3	≤ 0.25	≤ 1.5			3.7	3.7	3.7	4.0	5.8	7.0	7.0	5.5	5.0
				4	≤ 0.25	≤ 1.5			5.0	5.0	5.0	5.3	7.8	9.4	9.4	7.3	6.6
			Slot				185	RPM	45229	22614	11307	5654	2827	1885	1413	942	707
								Fz	0.00002	0.00004	0.00008	0.0002	0.0005	0.0009	0.0012	0.0014	0.0017
				2	1	≤ 1	(148-222)	Feed (ipm)	1.8	1.8	1.8	1.9	2.8	3.4	3.4	2.6	2.4
				3	1	≤ 0.5			2.7	2.7	2.7	2.9	4.2	5.1	5.1	4.0	3.6
				4	1	≤ 0.4			3.6	3.6	3.6	3.8	5.7	6.8	6.8	5.3	4.8
K	CAST IRONS Gray, Malleable, Ductile	≤ 220 Bhn or ≤ 19 HRc	Profile				335	RPM	81901	40950	20475	10238	5119	3413	2559	1706	1280
								Fz	0.00003	0.00006	0.00013	0.0003	0.0008	0.0015	0.0020	0.0024	0.0028
				2	≤ 0.50	≤ 1.5	(268-402)	Feed (ipm)	4.9	4.9	5.3	6.1	8.2	10.2	10.2	8.2	7.2
				3	≤ 0.25	≤ 1.5			7.4	7.4	8.0	9.2	12.3	15.4	15.4	12.3	10.7
				4	≤ 0.25	≤ 1.5			9.8	9.8	10.6	12.3	16.4	20.5	20.5	16.4	14.3
			Slot				245	RPM	59898	29949	14974	7487	3744	2496	1872	1248	936
								Fz	0.00003	0.00006	0.00013	0.0003	0.0008	0.0015	0.0020	0.0024	0.0028
				2	1	≤ 1	(196-294)	Feed (ipm)	3.6	3.6	3.9	4.5	6.0	7.5	7.5	6.0	5.2
				3	1	≤ 0.5			5.4	5.4	5.8	6.7	9.0	11.2	11.2	9.0	7.9
				4	1	≤ 0.4			7.2	7.2	7.8	9.0	12.0	15.0	15.0	12.0	10.5
N	ALUMINUM ALLOYS 2017, 2024, 356, 6061, 7075	≤ 150 Bhn or ≤ 7 HRc	Profile				880	RPM	215142	107571	53786	26893	13446	8964	6723	4482	3362
								Fz	0.00006	0.00013	0.00025	0.0006	0.0016	0.0030	0.0040	0.0048	0.0056
				2	≤ 0.50	≤ 1.5	(704-1056)	Feed (ipm)	25.8	28.0	26.9	32.3	43.0	53.8	53.8	43.0	37.6
				3	≤ 0.25	≤ 1.5			38.7	42.0	40.3	48.4	64.5	80.7	80.7	64.5	56.5
			Slot				640	RPM	156467	78234	39117	19558	9779	6519	4890	3260	2445
								Fz	0.00006	0.00013	0.00025	0.0006	0.0016	0.0030	0.0040	0.0048	0.0056
				2	1	≤ 1	(512-768)	Feed (ipm)	18.8	20.3	19.6	23.5	31.3	39.1	39.1	31.3	27.4
				3	1	≤ 0.5			28.2	30.5	29.3	35.2	46.9	58.7	58.7	46.9	41.1
	COPPER ALLOYS Alum Bronze, C110, Muntz Brass	≤ 140 Bhn or ≤ 3 HRc	Profile				485	RPM	118573	59286	29643	14822	7411	4941	3705	2470	1853
								Fz	0.00003	0.00006	0.00013	0.0003	0.0008	0.0015	0.0020	0.0024	0.0028
				2	≤ 0.50	≤ 1.5	(388-582)	Feed (ipm)	7.1	7.1	7.7	8.9	11.9	14.8	14.8	11.9	10.4
				3	≤ 0.25	≤ 1.5			10.7	10.7	11.6	13.3	17.8	22.2	22.2	17.8	15.6
				4	≤ 0.25	≤ 1.5			14.2	14.2	15.4	17.8	23.7	29.6	29.6	23.7	20.8
			Slot				350	RPM	85568	42784	21392	10696	5348	3565	2674	1783	1337
								Fz	0.00003	0.00006	0.00013	0.0003	0.0008	0.0015	0.0020	0.0024	0.0028
				2	1	≤ 1	(280-420)	Feed (ipm)	5.1	5.1	5.6	6.4	8.6	10.7	10.7	8.6	7.5
				3	1	≤ 0.5			7.7	7.7	8.3	9.6	12.8	16.0	16.0	12.8	11.2
				4	1	≤ 0.4			10.3	10.3	11.1	12.8	17.1	21.4	21.4	17.1	15.0

continued on next page

FRACTIONAL

2 Flute: Square, Double, Stub, Long, Ball, Corner Radius
3 Flute: Square, Ball, Tapered
4 Flute: Square, Double, Stub, Ball, Corner Radius
Tapered: Square, Radius



	Series 1, 3, 5, 14, 15, 16, 17, 23, 24, 59 Fractional	Hardness		Flutes	Ae x DC	Ap x DC	Vc (sfm)		DC • in 1/64	1/32	1/16	1/8	1/4	3/8	1/2	3/4	1
N	PLASTICS Polycarbonate, PVC, Polypropylene		Profile				880	RPM	215142	107571	53786	26893	13446	8964	6723	4482	3362
							(704-1056)	Fz	0.00006	0.00013	0.00025	0.0006	0.0016	0.0030	0.0040	0.0048	0.0056
				2	≤ 0.50	≤ 1.5		Feed (ipm)	25.8	28.0	26.9	32.3	43.0	53.8	53.8	43.0	37.6
				3	≤ 0.25	≤ 1.5			38.7	42.0	40.3	48.4	64.5	80.7	80.7	64.5	56.5
				4	≤ 0.25	≤ 1.5			51.6	55.9	53.8	64.5	86.1	107.6	107.6	86.1	75.3
			Slot				640	RPM	156467	78234	39117	19558	9779	6519	4890	3260	2445
							(512-768)	Fz	0.00006	0.00013	0.00025	0.0006	0.0016	0.0030	0.0040	0.0048	0.0056
				2	1	≤ 1		Feed (ipm)	18.8	20.3	19.6	23.5	31.3	39.1	39.1	31.3	27.4
				3	1	≤ 0.5			28.2	30.5	29.3	35.2	46.9	58.7	58.7	46.9	41.1
				4	1	≤ 0.4			37.6	40.7	39.1	46.9	62.6	78.2	78.2	62.6	54.8
	GRAPHITE		Profile				660	RPM	161357	80678	40339	20170	10085	6723	5042	3362	2521
							(528-792)	Fz	0.00006	0.00013	0.00025	0.0006	0.0016	0.0030	0.0040	0.0048	0.0056
				2	≤ 0.50	≤ 1.5		Feed (ipm)	19.4	21.0	20.2	24.2	32.3	40.3	40.3	32.3	28.2
				3	≤ 0.25	≤ 1.5			29.0	31.5	30.3	36.3	48.4	60.5	60.5	48.4	42.4
				4	≤ 0.25	≤ 1.5			38.7	42.0	40.3	48.4	64.5	80.7	80.7	64.5	56.5
			Slot				480	RPM	117350	58675	29338	14669	7334	4890	3667	2445	1834
							(384-576)	Fz	0.00006	0.00013	0.00025	0.0006	0.0016	0.0030	0.0040	0.0048	0.0056
				2	1	≤ 1		Feed (ipm)	14.1	15.3	14.7	17.6	23.5	29.3	29.3	23.5	20.5
				3	1	≤ 0.5			21.1	22.9	22.0	26.4	35.2	44.0	44.0	35.2	30.8
				4	1	≤ 0.4			28.2	30.5	29.3	35.2	46.9	58.7	58.7	46.9	41.1
S	SUPER ALLOYS (NICKEL, COBALT, IRON BASE) Inconel 601, 617, 625, 718, Incoloy 800, Monel 400,Rene, Waspalloy	≤ 300 Bhn or ≤ 32 HRc	Profile				65	RPM	15891	7946	3973	1986	993	662	497	331	248
							(52-78)	Fz	0.00002	0.00003	0.00006	0.0002	0.0004	0.0008	0.0010	0.0012	0.0014
				2	≤ 0.50	≤ 1.5		Feed (ipm)	0.6	0.5	0.5	0.7	0.7	1.1	1.0	0.8	0.7
				3	≤ 0.25	≤ 1.5			1.0	0.7	0.7	1.1	1.0	1.6	1.5	1.2	1.0
				4	≤ 0.25	≤ 1.5			1.3	1.0	1.0	1.4	1.4	2.1	2.0	1.6	1.4
			Slot				45	RPM	11002	5501	2750	1375	688	458	344	229	172
							(36-54)	Fz	0.00002	0.00003	0.00006	0.0002	0.0004	0.0008	0.0010	0.0012	0.0014
				2	1	≤ 1		Feed (ipm)	0.4	0.3	0.3	0.5	0.5	0.7	0.7	0.6	0.5
				3	1	≤ 0.5			0.7	0.5	0.5	0.7	0.7	1.1	1.0	0.8	0.7
				4	1	≤ 0.4			0.9	0.7	0.7	1.0	1.0	1.5	1.4	1.1	1.0
	TITANIUM ALLOYS Ti6Al4V, Ti6Al2Sn4Zr2Mo, Ti4Al4Mo2Sn0.5Si, Ti10Al2Fe3Al, Ti5Al53Mo3Cr, Ti7Al4Mo, Ti3Al8V6Cr4Zr4Mo, Ti6Al6V6Sn, Ti152 Cr3Sn3Al	≤ 350 Bhn or ≤ 38 HRc	Profile				180	RPM	44006	22003	11002	5501	2750	1834	1375	917	688
							(144-216)	Fz	0.00002	0.00004	0.00008	0.0002	0.0005	0.0009	0.0012	0.0014	0.0017
				2	≤ 0.50	≤ 1.5		Feed (ipm)	1.8	1.8	1.8	2.2	2.8	3.3	3.3	2.6	2.3
				3	≤ 0.25	≤ 1.5			2.6	2.6	2.6	3.3	4.1	5.0	5.0	3.9	3.5
				4	≤ 0.25	≤ 1.5			3.5	3.5	3.5	4.4	5.5	6.6	6.6	5.1	4.7
			Slot				130	RPM	31782	15891	7946	3973	1986	1324	993	662	497
							(104-156)	Fz	0.00002	0.00004	0.00008	0.0002	0.0005	0.0009	0.0012	0.0014	0.0017
				2	1	≤ 1		Feed (ipm)	1.3	1.3	1.3	1.6	2.0	2.4	2.4	1.9	1.7
				3	1	≤ 0.5			1.9	1.9	1.9	2.4	3.0	3.6	3.6	2.8	2.5
				4	1	≤ 0.4			2.5	2.5	2.5	3.2	4.0	4.8	4.8	3.7	3.4
H	TOOL STEELS A2, D2, H13, L2, M2, P20, S7, T15, W2	≤ 250 Bhn or ≤ 24 HRc	Profile				315	RPM	77011	38506	19253	9626	4813	3209	2407	1604	1203
							(252-378)	Fz	0.00002	0.00005	0.00009	0.0002	0.0006	0.0011	0.0015	0.0018	0.0021
				2	≤ 0.50	≤ 1.5		Feed (ipm)	3.1	3.9	3.5	3.9	5.8	7.1	7.2	5.8	5.1
				3	≤ 0.25	≤ 1.5			4.6	5.8	5.2	5.8	8.7	10.6	10.8	8.7	7.6
				4	≤ 0.25	≤ 1.5			6.2	7.7	6.9	7.7	11.6	14.1	14.4	11.6	10.1
			Slot				230	RPM	56230	28115	14058	7029	3514	2343	1757	1171	879
							(184-276)	Fz	0.00002	0.00005	0.00009	0.0002	0.0006	0.0011	0.0015	0.0018	0.0021
				2	1	≤ 1		Feed (ipm)	2.2	2.8	2.5	2.8	4.2	5.2	5.3	4.2	3.7
				3	1	≤ 0.5			3.4	4.2	3.8	4.2	6.3	7.7	7.9	6.3	5.5
				4	1	≤ 0.4			4.5	5.6	5.1	5.6	8.4	10.3	10.5	8.4	7.4

Bhn (Brinell) HRc (Rockwell C)
rpm = (Vc x 3.82) / DC
ipm = Fz x number of flutes x rpm
reduce speed and feed for materials harder than listed
for tapered end mills, base the speed on the largest diameter contacting the workpiece and the feed on the smallest diameter
limit cut depths of long and extra long flute mills to .05 x DC when slotting or profiling
reduce feed and Ae when finish milling (.02 x DC maximum)
refer to the SGS Tool Wizard® for complete technical information (www.kyocera-sgstool.com)