


# TECHNICAL DATA | WINNER |


## WB542 series

Feed Rate	General Cutting Speed					
Work Material	Alloy Steels, Carbon Steels (SCM, SNCM, S45C)		Prehardened Steels (NAK, CENA, KP4)		Hardened Steels (SKD, SKT, STAVAX)	
Hardness	≤ 35 HRC		35 ~ 45 HRC		45 ~ 55 HRC	
Strength	≤ 1100N / mm <sup>2</sup>		1100~1500N / mm <sup>2</sup>		1500~2000N / mm <sup>2</sup>	
Cutting Diameter (metric)	RPM	FEED	RPM	FEED	RPM	FEED
0.1	16,500	80	25,500	185	25,500	160
0.2	16,500	90	25,500	220	25,500	200
0.3	15,300	112	24,000	260	24,000	220
0.4	15,300	112	24,000	260	24,000	220
0.5	13,300	128	20,800	300	20,800	250
0.6	11,200	144	17,600	330	17,600	280
0.8	11,200	144	17,600	330	17,600	280
1.0	10,180	160	16,000	370	16,000	320
1.5	9,500	220	13,000	500	12,800	400
2.0	9,250	260	11,500	640	11,300	590
3.0	8,000	370	10,200	880	9,800	850
4.0	6,720	420	8,500	880	8,200	850
5.0	5,840	460	7,500	880	7,200	850
6.0	5,500	660	6,900	920	6,500	880
8.0	4,600	740	5,600	840	5,300	800
10.0	4,070	820	4,850	800	4,650	770
12.0	3,700	890	4,350	800	4,150	770

RPM = rev. / min.  
FEED = mm / min.



ap : D1~D6=0.2mm  
D8~D12=0.3mm  
ae : 0.2×D




ap : D1~D4=0.05×D  
D5~D8=0.25mm  
D10~D12=0.3mm  
ae : 0.1×D


# TECHNICAL DATA | WINNER |

Feed Rate	High Cutting Speed					
Work Material	Alloy Steels, Carbon Steels (SCM, SNCM, S45C)		Prehardened Steels (NAK, CENA, KP4)		Hardened Steels (SKD, SKT, STAVAX)	
Hardness	≤ 35 HRC		35 ~ 45 HRC		45 ~ 55 HRC	
Strength	≤ 1100N / mm <sup>2</sup>		1100~1500N / mm <sup>2</sup>		1500~2000N / mm <sup>2</sup>	
Cutting Diameter (metric)	RPM	FEED	RPM	FEED	RPM	FEED
0.1	16,500	80	25,500	185	25,500	160
0.2	16,500	90	25,500	220	25,500	200
0.3	15,300	112	24,000	260	24,000	220
0.4	15,300	112	24,000	260	24,000	220
0.5	13,300	128	20,800	300	20,800	250
0.6	11,200	144	17,600	330	17,600	280
0.8	11,200	144	17,600	330	17,600	280
1.0	10,180	160	16,000	370	16,000	320
1.5	9,500	220	13,000	500	12,800	400
2.0	9,250	260	11,500	640	11,300	590
3.0	8,000	370	10,200	880	9,800	850
4.0	6,720	420	8,500	880	8,200	850
5.0	5,840	460	7,500	880	7,200	850
6.0	5,500	660	6,900	920	6,500	880
8.0	4,600	740	5,600	840	5,300	800
10.0	4,070	820	4,850	800	4,650	770
12.0	3,700	890	4,350	800	4,150	770

RPM = rev. / min.  
FEED = mm / min.



ap : D1-D6=0.2mm  
D8-D12=0.3mm  
ae : 0.05×D



ap : D1-D4=0.05×D  
D5-D8=0.25mm  
D10-D12=0.3mm  
ae : 0.05×D